

OVERFILL EQUIPMENT INSPECTION – BALL FLOAT VALVE

NORTH DAKOTA DEPARTMENT OF ENVIRONMENTAL QUALITY DIVISION OF WASTE MANAGEMENT - UST PROGRAM SFN 62217 (09/2022)

Telephone: 701-328-5166 Fax: 701-328-5200 Email: <u>ndust@nd.gov</u> Website: <u>https://deg.nd.gov/wm</u>

This data sheet is for inspecting ball float valves. If a ball float is found to fail the inspection, another method of overfill must be used. See PEI/RP1200-17, Section 7 for inspection procedures.

Clear Form

FACILITY INFORMATION

Facility Name	Telephone Number		
Address	City	State	ZIP Code

TESTER INFORMATION

Name of Tester	Name of Company		
Address	City	State	ZIP Code
Telephone Number	Email Address		

BALL FLOAT VALVE INSPECTION

Date of Test:								
Tank ID								
Tank Volume, gallons								
Tank Diameter, inches								
Tank top fitting vapor- tight and leak-free?	🗌 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗌 Yes 🗌 No	🗌 Yes 🗌 No		
Ball float cage free of debris?	🗌 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗌 Yes 🗌 No	🗌 Yes 🗌 No		
Ball free of holes and cracks and moves freely in cage?	🗌 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗌 Yes 🗌 No	🗌 Yes 🗌 No		
Vent hole in pipe open and near top of tank?	🗌 Yes 🗌 No	🗌 Yes 🗌 No	🗆 Yes 🗌 No	🗆 Yes 🗌 No	🗌 Yes 🗌 No	🗌 Yes 🗌 No		
Ball float pipe proper length to restrict flow at 90% capacity?	🗆 Yes 🛛 No	🗆 Yes 🗌 No	🗌 Yes 🗌 No					
Pass/Fail Criteria: A "No" to any item indicates a test failure.								
Test Results	🗌 Pass 🗌 Fail							
Comments:								